

SERIES GR

THE GARAGE READY RESIDENTIAL
INFRARED HEATER




SUPERIOR
RADIANT PRODUCTS

**HIGH
EFFICIENCY**
FUEL SAVINGS
UP TO 50%



Shown with optional
deco grill kit



Keep your garage or
workshop warm and comfortable
with **SRP's high efficiency
infrared heater**

FEATURES

- **UNPACK, HANG, CONNECT**
It's as easy as 1, 2, 3.
- Rates 30,000 and 45,000 BTU/HR
- Natural Gas and LPG
- PSC blower motor
- Preassembled construction
 - no loose parts
 - simplified installation
- Direct spark ignition (DSI)
- Self diagnostic ignition module
- Superior ignition system for utmost in reliability
- **Balanced flue construction**
 - one wall opening
 - maximum safety
 - minimum installation costs
- Hang horizontal or at 45 degrees
- Aluminized (HT) radiant tube
- Thermostat and gas flex connector included
- Outdoor and deco grill kits available
- Vertical vent adapter kit available
- Low cost to install

SAVING ENERGY FOR FUTURE GENERATIONS
WWW.SUPERIORRADIANT.COM

SERIES GR INFRARED HEATERS SPECIFICATIONS

MODEL	RATE BTU/HR	SHIP WT.	DIMENSIONS
GR-30	30,000	109 lbs (50kg)	17.5" x 8" x 118"
GR-45	45,000	109 lbs (50kg)	17.5" x 8" x 118"

ELECTRICAL RATING	120 VAC 60 Hz 1A plug connector
GAS CONNECTION	1/2" NPT
TUBE DIAMETER	Combustion air 4" Flue 2" (Concentric)
MINIMUM GAS INLET	Nat gas 5.0" W.C. LPG 11.0" W.C.

STANDARD EQUIPMENT INCLUDES

- Pre-assembled burner and heat exchanger
- Ceiling suspension hardware
- Gas flex connector
- Thermostat
- 8' Venting Kit



APPROVAL STANDARDS

The Series GR heater by Superior Radiant Products has been specifically designed for residential garage and workshop applications and approved to CSA's stringent residential requirements.


Series GR high thermal efficiency 82+% combines with radiant's sun-like warmth keeping people comfortable at lower thermostat settings, resulting in fuel savings of up to 50% over conventional forced - air heaters.

BALANCED FLUE CONSTRUCTION

The flue pipe of the Series GR heater by Superior Radiant Products is concentrically inside the combustion air inlet pipe. This construction:


- Preheats the combustion air, making the Series GR heater the most efficient heater of its class.
- Limits wall penetrations to one 4 inch hole, making installation simple and economical.
- Exposes inlet air and outlet gases to the same pressure conditions resulting in unparalleled safety and trouble free operation.

DIMENSIONS (Inches)



CLEARANCES TO COMBUSTIBLES (Inches)

MODEL	GR-30				GR-45			
	A	B	C	D	A	B	C	D
Configuration	A	B	C	D	A	B	C	D
Horizontal	2	18	36	18	2	18	50	18
45° Tilt	2	2	33	33	3	3	48	48



For more information please refer to the installation manual

Visit our website for I/O manual



SUPERIOR
RADIANT PRODUCTS



Superior Radiant Products Ltd.
563 Barton Street
Stoney Creek, ON L8E 5S1 Canada

Superior Radiant Products Inc.
315 N Madison Street
Fortville, IN 46040 USA

1 800 527 HEAT(4328) | tel 1 905 664 8274 | fax 1 905 664 8846
sales@superiorradiant.com | www.superiorradiant.com

SAVING ENERGY FOR FUTURE GENERATIONS

DISTRIBUTOR